




Benchstat


Premium ESD work bench mat, with triple layer construction




- Superior performance static-dissipative work surface matting.
- Textured vinyl top surface is chemical and scratch resistant.
- Buried middle layer conducts ESD protecting operatives and components.
- Foam base cushions dropped components, while providing a comfortable work surface.
- Grounded via a 10 mm male stud fitted to the mat.
- Meets or exceeds IEC61340-5-1 resistance requirements.
- Point to point resistance (Rp-p): $3.1 \times 10^7 \Omega$
- Resistance to a groundable point (Rgp): $1.4 \times 10^7 \Omega$
- Also available in a handy kit with accessories included.



Styles Available



Grey



Blue

Parts

Part Number	Size	Colour	Weight (kg)
IS020001	0.6 m x 30 m	Blue	38
IS020001C	0.6 m x per linear metre (max. 30 m)	Blue	1.4

Technical Specifications

Material	Triple layer vinyl with a buried conductive layer
Surface Finish	Light Pebble
Product Height	3.2 mm

Part Number	Size	Colour	Weight (kg)
IS020002	0.9 m x 30 m	Blue	67.2
IS020002C	0.9 m x per linear metre (max. 30 m)	Blue	2.24
IS020003	1.2 m x 30 m	Blue	87.5
IS020003C	1.2 m x per linear metre (max. 30 m)	Blue	2.91
IS020004	0.6 m x 1.2 m	Blue	1.52
IS060001	0.6 m x 30 m	Grey	38
IS060001C	0.6 m x per linear metre (max. 30 m)	Grey	1.4
IS060002	0.9 m x 30 m	Grey	67.2
IS060002C	0.9 m x per linear metre (max. 30 m)	Grey	2.24
IS060003	1.2 m x 30 m	Grey	87.5
IS060003C	1.2 m x per linear metre (max. 30 m)	Grey	2.91
IS060004	0.6 m x 1.2 m	Grey	1.52

Min. Operating Temperature	-28°C
Max. Operating Temperature	+71°C
Resistance to Chemicals	PVC is resistant to many different chemicals, alkalis and general industrial chemicals. PVC resists alcohols, aliphatic hydrocarbons, oils, weak acids, strong mineral acids and alkalis. PVC resists oil and grease if properly cleaned. PVC does not resist organic solvents, ketones, esters and aromatic hydrocarbons. Please contact us for more specific details
Environmental Resistance	Suitable for dry indoor environments
Typical Applications	Work bench surfaces within the electronics industry or any environment that requires ESD protection for their products and workplace.
Installation Method	Loose lay - must be connected via grounding wire and accessories
Accessories	ESD kits and accessories available
Cleaning Method	Brush or wipe the top surface. Isopropyl Alcohol or soap and warm water may also be used for contaminated surfaces.
COO (Country of Origin)	US

Additional Information



Benchstat ESD Test IEC 61340.jpeg

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com