



## COBAelite® Bubble

Excellent fatigue relief with superior resilience



- Improve comfort when standing in the workplace.
- Raised surface stimulates blood circulation and foot movement.
- Superior material ensures durability.
- Ramped edges help avoid creating a trip risk.
- Loose lay – can easily be installed in a wide array of workplaces.
- Fire tested to BS EN 13501-1.



### Parts

Part Number	Size	Colour	Weight (kg)
SE010001	0.6 m x 0.9 m	Black	2
SE010003	0.9 m x 1.2 m	Black	4.5
SE010010	Special size	Black	

### Technical Specifications

Material	PU
Surface Finish	Bubble
Product Height	15 mm
Product Weight	2.5 kg ± 0.2
Min. Operating Temperature	-40°C
Max. Operating Temperature	+80°C
Resistance to Chemicals	PU offers limited resistance to chemicals and oils
Environmental Resistance	Suitable for dry indoor environments
UV Resistance	Yes

<b>Typical Applications</b>	General industrial, Retail
<b>Installation Method</b>	Loose lay
<b>Cleaning Method</b>	Brush down, vacuum clean and wipe with wet cloth
<b>Fire Tested to</b>	BS EN 13501-1 Class Efl - s1
<b>COO (Country of Origin)</b>	DE

## Additional Information



COBAelite BS EN 13501 Fire Test



COBAelite EN ISO 11925 Fire Test



COBAelite EN ISO 9239 Fire Test

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)116 240 1088 or email [sales@cobaeurope.com](mailto:sales@cobaeurope.com)

[www.cobaeurope.com](http://www.cobaeurope.com)