



COBAelite® ESD

Bubble surfaced mat to tackle fatigue in ESD sensitive areas









- Static-dissipative anti-fatigue mat for comfort and safety.
- Conductive buried layer neutralises static charge, protecting
 components.
- Comfortable bubbled surface promotes subtle movement further reducing fatigue.
- Grounded via a 10 mm male stud fitted to the mat.
- Meets or exceeds IEC61340-5-1 resistance requirements.
- Resistance to a groundable point (Rgp): 2.4 x $10^6 \Omega$











Parts

| Part Number | Size | Colour | Weight (kg) |
|-------------|---------------|--------|-------------|
| SE010001ESD | 0.6 m x 0.9 m | Black | 2 |
| SE010003ESD | 0.9 m x 1.2 m | Black | 4.5 |
| SE010010ESD | Special size | Black | |

Technical Specifications

| Material | PU |
|-------------------------------|--|
| Surface Finish | Bubble |
| Product Height | 14 mm |
| Product Weight | 3 kg ± 3% |
| Min. Operating Temperature | -40°C |
| Max. Operating Temperature | +80°C |
| Resistance to Chemicals | PU offers limited resistance to chemicals and oils |
| Environmental Resistance | Suitable for dry indoor environments |
| UV Resistance | Yes |

| Accessories | ESD accessories available |
|-------------------------|------------------------------|
| Fire Tested to | BS EN 13501-1 Class Efl - s1 |
| COO (Country of Origin) | DE |

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com