





COBAAscape

Oil-resistant matting for kitchens and food processing environments



- Excellent resistance to cooking oils, chemicals and grease.
- Raised surface provides slip resistance and firm footing in greasy or oily conditions.
- Multi-purpose doormat that scrapes away dirt and also retains water.
- Raised pattern scrapes away dirt and debris from footwear.
- Non-slip, helping to reduce the risk of slipping on wet floors.
- Holds up to 2.6 litres of water/ m² or 1.5 kg of dry dust/ m².
- Bevelled edging as a safety standard.
- Slip tested to DIN 51130.



Parts

Part Number	Size	Colour	Weight (kg)
CS010001	0.85 m x 0.75 m	Black	5.8
CS010002	0.85 m x 1.5 m	Black	6
CS010003	0.85 m x 3 m	Black	10.5
CS010004	1.15 m x 1.75 m	Black	8.5

Technical Specifications

Material	NBR
Surface Finish	Raised rectangular cleats
Product Height	6 mm
Product Weight	4.2 kg / m ²
Min. Operating Temperature	-20°C
Max. Operating Temperature	+70°C
Resistance to Chemicals	Resistant to many chemicals, alkalis, detergents, oils, machine coolants and general industrial coolants.

Rubber may swell in polar solvents.

Environmental Resistance	Suitable for wet and dry environments, indoors or outdoors
UV Resistance	Yes
Typical Applications	Food manufacturing, Kitchens, General industrial. Entrance areas.
Installation Method	Loose Lay
Cleaning Method	0.75 m x 0.85 m can be washed in standard domestic washing machines. All other sizes can be laundered in commercial washing machines or hosed down with a high pressure washer.
COO (Country of Origin)	IN
Slip Tested to	DIN 51130 - R10

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeeurope.com

www.cobaeeurope.com