

Loopermat

Distinctive looped design matting

- Soft, compounded PVC looped surface traps dirt, debris and moisture.
- Cleaning is easy – simply shake to release the debris.
- Heavy Unbacked for recessed matwells featuring a mesh underlay to prevent shrinkage.
- Medium Backed for loose lay applications with PVC backing.
- Fire tested to DIN 4102 (B1).
- UV stabilised for fade resistance.

Colour Options



Backed

Unbacked



Technical Specification

Material:	PVC
Product Height:	9mm backed or 14mm unbacked
Flame Retardancy:	Fire tested to DIN 4102 Part 14
Operating Temperature:	-10°C to 60°C
Country of Origin:	China

Unbacked			
Sizes	Blue	Grey	Weight
0.9m x 9m	LU020909	LU060909	38.00 kg
0.9m x 9m	LU021209	LU061209	52.75 kg
0.9m x per linear metre (max. 9m)	LU020909C	LU060909C	4.80 kg
1.2m x per linear metre (max. 9m)	LU021209C	LU061209C	5.86 kg

Backed		
Sizes	Grey	Weight
0.9m x 9m	LB060909	26.30 kg
0.9m x 9m	LB061209	33.00 kg
0.9m x per linear metre (max. 9m)	LB060909C	3.20 kg
1.2m x per linear metre (max. 9m)	LB061209C	3.20 kg