



## Fatigue-Step Interlocking rubber safety tiles

- Interlocking rubber tile system.
- Ideal for increasing safety at outdoor play areas.
- Tested to Critical Fall Height of 0.6m (BS EN 1177:1998).
- Comfortable, yet resilient rubber.
- Excellent drainage in wet conditions.
- Conforms to Slip Resistance Test EN13552 Category R10.



## Technical Specification

<b>Material:</b>	Natural rubber
<b>Surface Finish:</b>	Smooth with 22mm holes to allow drainage
<b>Product Height:</b>	18mm
<b>Operating Temperature:</b>	-20°C to +160°C
<b>Resistant to Chemicals:</b>	Natural rubber offers limited resistance to chemicals and oils
<b>Environmental Resistance:</b>	Suitable for wet and dry environments
<b>UV Resistance:</b>	Yes
<b>Typical Applications:</b>	Ideal non-slip surface for play areas
<b>Installation Method:</b>	Loose lay interlocking tiles
<b>Accessories:</b>	Bevelled edge/ corners (installation guide below)
<b>Cleaning Method:</b>	Pressure hose with mild detergent or pass through commercial dishwasher
<b>Product Performance:</b>	Conforms to Slip Resistance Test EN 13552 Category R10
<b>Country of Origin:</b>	India

Size	Part Code	Weight
Tile 0.9m x 0.9m	SS010001	9.95 kg