

COBAstat®

Static-dissipative anti-fatigue mat

- Durable floor mat to protect operatives from static build-up.
- Anti-fatigue standing surface for improved comfort.
- Grounded via a 10mm male stud fitted to the mat.
- Maximum performance when used with grounding wire.
- Actual resistance: $1 \times 10^9\Omega$ to $1 \times 10^{10}\Omega$.



Technical Specification

Material:	Virgin Closed Cell PVC Foam (Homogenous)
Surface Finish:	Pebble
Product Height:	9mm
Operating Temperature:	0°C to +60°C
Environmental Resistance:	Suitable for dry indoor environments
Typical Applications:	Around machinery where static build up is common. Not to be used in High Voltage Areas exceeding 240 Volts
Installation Method:	Loose lay
Accessories:	Floor Kits where required
Cleaning Method:	Brush or mop the top surface
Flame Retardancy:	Conforms to FMVSS 302. Will not burn after the ignition source is removed. When 'forced' to burn, Carbon Monoxide, Carbon Dioxide and Hydrogen Chloride fumes are emitted
Country of Origin:	China

Sizes	Part Code	Weight
0.6m x 0.9m	AS060001	2.00 kg
0.9m x 1.5m	AS060002	4.50 kg
0.9m x 18.3m	AS060003	55.00 kg
0.9m x per linear metre (max. 18.3m)	AS060003C	2.00 kg

