

# COBAGRIP®

COBAGRIP is a range of UV stabilised GRP sheets, treads and stair nosing designed to offer exceptional levels of slip-resistance both indoors and out, while having outstanding wear and tear qualities. It is an ideal underfoot safety solution for pedestrian and factory walkways, access ramps, gangways and bridges.

The Silicone Carbide 'gritted' top surface provides effective underfoot grip and is resistant to most solvents and chemicals. It is manufactured using flame retardant materials. Easy to install, simply bond or screw to the existing floor surface, COBAGRIP is a cost-effective means of refurbishing damaged or slippery floors. Easy to clean (pressure wash).

## Slip Tested

COBA Europe's range of GRP products have been tested for slip resistance. Ramp Slip Tested to R13 in accordance with DIN 51130: 2010. Pendulum Slip Tested in accordance with BS 7976-2: 2002.

- PTV 79 in dry conditions
- PTV 73 in wet conditions

## COBAGRIP® Sheet

**Ideal solution to combat slip hazards such as spilt liquids or ice**

- Available in a range of colours to meet all DDA requirements.
- Suitable for use with forklift traffic.
- Simply bond or screw to the existing floor surface.
- Colour options: black, grey and yellow.

## COBAGRIP® Light

**Manufactured from flexible grp sheet**

- Ideal for use on undulating surfaces.
- Can also be used in food production areas.

### Colour Options



Black



Grey



Yellow



## Technical Specification

<b>Material:</b>	Silicone Carbide
<b>Product Height:</b>	5mm or 3mm
<b>Installation Method:</b>	Bond or screw to surface
<b>Cleaning Method:</b>	COBAGRIP should be almost maintenance free in most outside environments. Natural elements will have the effect of cleaning COBAGRIP. Brushing and flushing with a mild detergent solution may be desirable now and again to restore appearance
<b>Product Performance:</b>	Slip tested to R13 in accordance with BS 7976-2:2002 • PTV 79 in dry conditions • PTV 73 in wet conditions
<b>Operating Temperature:</b>	-10°C to 80°C
<b>Flame Retardancy:</b>	Fire tested to EN 9239-1:2010
<b>Country of Origin:</b>	China

Sheet (5mm)	Black	Grey	Yellow	Weight
1.2m x 2.4m	GRP010001	GRP060001	GRP070001	23.60 kg
1.2m x 1.2m	GRP010002	GRP060002	GRP070002	10.08 kg
0.8m x 1.2m	GRP010003	GRP060003	GRP070003	7.70 kg
Light (3mm)	Black	Grey	Yellow	Weight
1.2m x 2.4m	GRP010001L	GRP060001L	GRP070001L	17.00 kg
1.2m x 1.2m	GRP010002L	GRP060002L	-	10.08 kg
0.8m x 1.2m	GRP010003L	GRP060003L	-	6.00 kg