





Fatigue-Step

Economical anti-fatigue matting, ideal for bars and kitchens



- Provide standing relief to all workers with this economical anti-fatigue mat.
- Raised circular surface provides effective slip resistance.
- Open drainage holes capture spilt drinks, food or other debris to help prevent slips.
- Moulded ramped edges to reduce the risk of trips and allow wheeled access.
- Made from hardwearing rubber for durability.
- Slip tested to DIN 51130.



Parts

| Part Number | Size | Colour | Weight (kg) |
|-------------|-----------------------|--------|-------------|
| SS010001 | 0.9 m x 0.9 m | Black | 9.95 |
| SS010006 | 0.9 m x 0.9 m (14 mm) | Black | |
| SS010007 | 0.9 m x 0.9 m | Black | 10 |

Technical Specifications

| | |
|-----------------------|----------------------------------------------|
| Material | Rubber mix, including >50% recycled material |
| Surface Finish | Textured with holes to allow drainage |
| Product Height | 18 mm |
| Hole Size | 22 mm |
| Min. Operating | -20°C |

| | |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Temperature | |
| Max. Operating Temperature | +130°C |
| Resistance to Chemicals | Natural rubber offers limited resistance to chemicals and oils |
| Environmental Resistance | Suitable for wet and dry environments. Will withstand welding splatter and spillages of other hot materials. |
| UV Resistance | Yes |
| Typical Applications | All industrial environments, Bars, Catering environments, Areas where swarf is prevalent. Children's play areas. |
| Installation Method | Loose lay interlocking tiles |
| Accessories | Bevelled corner edges |
| Cleaning Method | Wash with cold water, use vacuum cleaner or use pressure pump to remove dirt |
| COO (Country of Origin) | IN |
| Storage and application | Store at room temperature, free from deformations. |
| Tensile Strength | 3 to 3.5 MPa |
| Notes | Silicone is used in the production process of the mats and a residue will possibly be left on the mat. This can be washed off using hot soapy water. |
| Slip Tested to | DIN 51130 - R10 |

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com