







Flexi-Deck

Anti-slip floor tiles for increased safety on wet floors



- Used in a wide range of environments, from industrial to leisure.
- Anti-slip surface reduces slip risks in wet conditions.
- The design allows the floor tiles to stay dry on the top surface for a safer footing.
- Open holes and specially designed underside studs have exceptional water drainage properties.
- Interlocking tile system – cover as small or larger floor area as required.
- Tiles are flexible and easy to move for ease of cleaning, relocation or individual replacement.
- Material offers a number of hygienic and durability benefits.



Parts

Part Number	Size	Colour	Weight (kg)
FD010001	30 cm x 30 cm	Black	3.8
FD010002F3		Black	0.23
FD010002M3		Black	0.23
FD010004		Black	0.06
FD020001	30 cm x 30 cm	Blue	3.8

Technical Specifications

Material	PVC
Product Height	13 mm
Min. Operating Temperature	-20°C
Max. Operating	+95°C

Part Number	Size	Colour	Weight (kg)
FD020002F3		Blue	0.23
FD020002M3		Blue	0.23
FD020004		Blue	0.06
FD030001	30 cm x 30 cm	Red	3.8
FD030002F3		Red	0.23
FD030002M3		Red	0.2
FD030004		Red	0.06
FD040001	30 cm x 30 cm	Green	3.8
FD040002F3		Green	0.23
FD040002M3		Green	0.2
FD040004		Green	0.06
FD060001	30 cm x 30 cm	Grey	3.8
FD060002F3		Grey	0.23
FD060002M3		Grey	0.23
FD060004		Grey	0.06

Temperature	
	PVC is resistant to many different chemicals, alkalis and general industrial chemicals. PVC resists alcohols, aliphatic hydrocarbons, oils, weak acids, strong mineral acids and alkalis. PVC resists oil and grease if properly cleaned. PVC does not resist organic solvents, ketones, esters and aromatic hydrocarbons. Please contact us for more specific details
Resistance to Chemicals	
Environmental Resistance	Suitable for wet and dry indoor environments
Typical Applications	Suitable for floors in work rooms and work areas where there is an increased risk of slipping. Can also be used on shelving. Changing rooms, Showers.
Installation Method	Loose lay interlocking tiles
Accessories	Edges and corners
Cleaning Method	Easily cleaned with hot soapy water or pressure washer
COO (Country of Origin)	CN

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeeurope.com

www.cobaeeurope.com