



## High-Duty

Reduce standing fatigue at larger or oily workstations



- A very comfortable alternative to cold hard floors.
- Open holes capture spilt liquids and swarf.
- Manufactured from a blend of rubber for better than average resistance to oil.
- Available in standard mats, edged on all sides, or as interlocking modules for larger areas.
- Raised circular surface gives excellent underfoot grip.
- Slip tested to DIN 51130.

## Parts

Part Number	Size	Colour	Weight (kg)
HI010001	0.9 m x 1.5 m	Black	8.9
HI010002	0.9 m x 1.5 m	Black	9
HI010003	0.9 m x 1.5 m	Black	9
HI010004	0.9 m x 1.5 m	Black	9
HI010005	0.9 m x 1.5 m	Black	9

## Technical Specifications

<b>Material</b>	Natural rubber/25% NBR compound
<b>Recycled Material Content %</b>	62.07%
<b>Natural Material Content %</b>	30
<b>Surface Finish</b>	Circular pattern construction for extra grip and holes to allow drainage
<b>Product Height</b>	12 mm
<b>Product Weight</b>	9.2 kg
<b>Max.</b>	+70°C

<b>Operating Temperature</b>	
<b>Resistance to Chemicals</b>	Limited resistance to chemicals
<b>Environmental Resistance</b>	Suitable for wet and dry environments
<b>UV Resistance</b>	Moderate
<b>Typical Applications</b>	General industrial, Bars, Catering environments, Machine tool areas where swarf is prevalent
<b>Installation Method</b>	Loose lay interlocking mats
<b>Cleaning Method</b>	For regular maintenance, hose with water. For excessive dirt scrub with a mild detergent and rinse.
<b>COO (Country of Origin)</b>	IN
<b>Tensile Strength</b>	ASTM D412, 3 (+/-1)Nm/mm <sup>2</sup>
<b>Elongation</b>	ASTM D412, 200% (+/-50%)
<b>Application Temperature</b>	18°C to 65.5°C
<b>Slip Tested to</b>	DIN 51130 - R10
<b>Manufacturing process</b>	Rubber moulding

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email [sales@cobaeeurope.com](mailto:sales@cobaeeurope.com)

[www.cobaeeurope.com](http://www.cobaeeurope.com)