



K-Mat

Reduce fatigue and slips on greasy floors



- Contains nitrile to offer the best resistance to oils and chemicals.
- Ideal for food processing and manufacturing locations due to its excellent resistance to grease, fats and detergents.
- Easily cleaned in a commercial washing machine.
- Raised pattern surface for exceptional slip-resistance (tested to DIN 51130).
- Open holes efficiently drain liquids and capture debris.
- Hygienic anti-microbial properties make it suitable for food processing locations.



Parts

Part Number	Size	Colour	Weight (kg)
KM010001	0.92 m x 1.53 m	Black	7.5
KM010002	0.92 m x 2.9 m	Black	10

Technical Specifications

Material	NBR
Surface Finish	Cross-grip
Product Height	9 mm
Product Weight	7.75 kg
Hole Size	12.5 mm
Min. Operating	0°C

Temperature	
Max. Operating Temperature	+100°C
Resistance to Chemicals	Resistant to oil
Environmental Resistance	Suitable for kitchens and oily indoor environments
UV Resistance	Yes
Typical Applications	Food manufacturing, Kitchens, General industrial, Machine tool areas where swarf is prevalent
Installation Method	Loose lay
Cleaning Method	Pressure hose
COO (Country of Origin)	LK
Tensile Strength	5 MPa
Elongation	400%
Application Temperature	-30°C to 90°C
Slip Tested to	DIN 51130 - R11
Manufacturing process	Compression moulding

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeeurope.com

www.cobaeeurope.com