


Plan.e

Robust aluminium entrance matting with low profile



- Durable linking joints for ease of handling/fitting.
- Suitable for high volume footfall in commercial locations.
- Available with most standard carpet insert options.
- Custom-made to order.
- Fire tested to BS EN 13501-1 and slip tested to BS 7976-2.



Styles Available





Parts

Part Number	Size	Colour	Weight (kg)
PLANE1	Special	Needlepunch and Alba	

Technical Specifications

Material	Aluminium channels with carpet inserts
Backing	High density PE60
Surface Finish	Carpet
Product Height	12 mm
Product Weight	13.16 kg / m ²
Durability	Heavy to very heavy traffic entrances
Environmental Resistance	Suitable for indoor environments only
UV Resistance	Yes
Typical Applications	Entrance areas
Installation Method	Installed in to recessed well
Other Product Performance Information	Uniform floor load = 14.36 KN/ m ² . Wheel load 159 kg per wheel
Fire Tested to	Alba inserts: BS EN 13501-1 Class Cfl – s1. Needlepunch inserts: BS EN 13501-1 Class Efl – s1.
COO (Country of Origin)	UK
Notes	Slip resistance specifications are based on the correct direction of travel i.e. perpendicular to the rails and inserts.
Slip Tested to	BS 7976-2 – low slip potential

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com