



Premier Plus

Interlocking carpet entrance tiles to keep internal floor coverings clean and slip free













- Quality needlepunch carpet inserts available in two colours, which effectively scrape dirt and wipe moisture.
- Tiles simply clip together on site for ease of transportation and installation.
- Move, clean or replace individual tiles they clip together with ease.
- Tiles offer flexibility in the size and shape which can be covered.
- Easily cut to shape, so you can fit to any space and install faster with fewer specialist tools.
- Fire tested to BS EN 13501-1 and slip tested to BS 7976-2.

















Styles Available





Charcoal Grey

Parts

Part Number	Size	Colour	Weight (kg)
PMP010101	29 cm x 44 cm	Charcoal	1.2
PMP010101C	30 cm x 45 cm	Charcoal	1.2
PMP010601	29 cm x 44 cm	Grey	1.2
PMP010601C	30 cm x 45 cm	Grey	1.2

Technical Specifications

Material	Polypropylene carpet in PVC tile		
Product Height	14 mm		
Environmental Resistance	Suitable for dry environments		
Typical Applications	Entrance areas		
Installation Method	Installed in to recessed well		
Fire Tested to	BS EN 13501-1 Class Efl - s2		
COO (Country of Origin)	UK		
Guarantee	5 years		
Notes	Slip resistance specifications are based on the correct direction of travel i.e. perpendicular to the channels and inserts.		
Slip Tested to	BS 7976-2 - low slip potential		
Tile height	12.5 mm		

Get in touch | 10 order FREE samples or arrange a site visit please call +44 (0) 1788 228 555 or email sales@cobaeurope.com