



Solid Vinyl

Textured multi-purpose vinyl matting







- An economical floor covering for many different applications when a thinner vinyl product is required.
- Versatile, can be used on floors and workbenches.
- Features a distinctive pyramid patterned anti-slip surface for personal and component protection.
- Good sound insulation properties.







Parts

Part Number	Size	Colour	Weight (kg)
SV010001	1.22 m x 5 m	Black	18
SV010002	1.22 m x 10 m	Black	38
SV010002C	1.2 m x per linear metre	Black	5

Technical Specifications

Material	PVC
Surface Finish	Pyramid pattern
Product Height	3 mm
Min. Operating Temperature	-15°C
Max. Operating Temperature	+60°C
	PVC is resistant to many different chemicals, alkalis and general industrial chemicals. PVC resists alcohols, aliphatic hydrocarbons, oils, weak acids,
Resistance to Chemicals	strong mineral acids and alkalis. PVC resists oil and grease if properly cleaned. PVC does not resist organic solvents, ketones, esters and aromatic hydrocarbons. Please contact us for more specific details
	grease if properly cleaned. PVC does not resist organic solvents, ketones, esters and aromatic hydrocarbons. Please contact us for more specific

Resistance		
Typical Applications	Walkways, Workbench tops	
Installation Method	Loose lay	
Cleaning Method	Pressure hose with use of mild detergent	
COO (Country of Origin)	CN	

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com