

Tough Deck

Recycled drainable workplace tiles










- · Non-slip interlocking decking for wet areas.
- Combination of substantial product height and large holes offers excellent drainage.
- An economical yet heavy-duty matting solution.
- Easy DIY installation with connectors that conceal joins.
- Ideal for industrial use, especially in areas prone to liquid spillage.
- Ramped edges to prevent trips are available in black or yellow.
- Provides entry level anti-fatigue properties.
- Slip tested to DIN 51130.







Parts

Part Number	Size	Colour	Weight (kg)
TDC010001	0.18 m x 0.18 m	Black	1.168
TDC070001C	0.18 m x 0.18 m	Yellow	1.6
TDE010001F	0.48 m x 0.18 m	Black	1
TDE010001M	0.48 m x 0.18 m	Black	1
TDE070001F	0.48 m x 0.18 m	Yellow	1.2
TDE070001M	0.48 m x 0.18 m	Yellow	1.4
TDT010001	0.48 m x 0.48 m	Black	1.95

Technical Specifications

Material	Recycled rubber and plastic	
Product Height	20 mm	
Product Weight	1.95 kg	
Hole Size	16 mm	
COO (Country of Origin)	South Africa	
Slip Tested to	DIN 51130 - R10	
Max recommended contact pressure:	1.85 MPa	