




## Tough-Lock ESD


Interlocking electrostatic dissipative floor tiles



- The resilient PVC material is suitable for both heavy and light industrial use, including withstanding the weight of most forklift trucks.
- ESD properties help protect personnel and components.
- Meets or exceeds BS EN 61340-5-1 Edition 2 2016-05 resistance requirements.
- Tiles are easy to install, with a simple interlocking system.
- Textured surface.
- We can incorporate almost any logo or symbol into your Tough-Lock floor to create a permanent and highly visual message. Logo tiles are cut by CNC water jet for precision.
- Bevelled edging is available to add that finishing touch.
- Surface Resistance:  $2.2 \times 10^4 \Omega / \text{m}^2 - 3 \times 10^6 \Omega$ .
- Resistance to a groundable point:  $2.9 \times 10^4 \Omega - 5.7 \times 10^5 \Omega$ .



## Styles Available



Textured Grey

Part Number	Size	Colour	Weight (kg)
TLS	0.5 m x 0.5 m x 7 mm	Grey	2.25

Material	PVC
Surface Finish	Textured
Min. Operating Temperature	-15°C
Max. Operating Temperature	+30°C
Resistance to Chemicals	Resistant to most chemicals
Environmental Resistance	Suitable for indoor environments
Typical Applications	Electrostatic sensitive areas
Installation Method	Interlocking tiles - loose lay or bonded
Accessories	Bevelled edging
COO (Country of Origin)	UK (N.Ire.)
Manufacturing process	Injection Moulding

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email [sales@cobaeeurope.com](mailto:sales@cobaeeurope.com)

[www.cobaeeurope.com](http://www.cobaeeurope.com)